

# Additional 2" pc

Stainhandler – Additional 2' Pieces

Protect the appearance of that new or just cleaned roof with Stainhandler Roof Protector Zinc Strips

---

## **E-6000 INDUSTRIAL ADHESIVE CAULK.**

1 tube of adhesive will do 10 pieces (20 feet) of strips. 10.2 fl oz. Clear.

---

## **MX3 WALLPAPER REMOVER**

**DO NOT DILUTE:** This product is ready to use. Contents will strip two 13' x 14' rooms or 864 sq. ft. Shelf life is unlimited. No heating is needed.

**PREPARATION:** Cover carpet and furniture with drop cloth if needed. When working in small closed-in areas use adequate ventilation. Do not allow mix to dry on glass, ceramic tile or bare metals. Remove at once to prevent streaking. If streaks appear, try wet 00 steel wool to remove. Using a wallpaper scoring tool, thoroughly score paper from top to bottom and side to side to allow solution to get behind paper.

**TO REMOVE PAPER:** Using a hand trigger sprayer, a garden type

sprayer or a sponge, apply a generous amount of solution to entire surface. Dissolves paste on contact. Wait 90 seconds, open up a seam or loosen a small area of paper at top of wall with a small paint scraper. Paper will peel off in large pieces or whole sections. If any residue is left on wall, baseboard, furniture or carpet, spray on solution and wipe with wet cloth. No rewetting of paper is needed unless a long waiting period ensues. Will remove up to 3 layers of paper.

If paper was applied to unprimed wallboard, it will peel off without damage to board unless scored too deep. Gently score paper.

Excellent for removing old dried paste from walls and other surfaces regardless of how thick or old paste may be. It quickly dissolves paste for easy removal. Just spray and wipe with wet cloth.

Some borders may be difficult to remove because they were hung with a non-water soluble adhesive. In these cases, it may require prolonged soaking. This bottle may refill the 1 quart bottle of MX-3 Wallpaper Remover. Do not let mix dry on glass. Cover carpets and furniture if needed. If adhesive residue is left on wall, spray on solution and wipe with wet cloth.

**CAUTION:** Keep out of reach of children. Avoid contact with skin and eyes. If eye contact occurs, flush with water for 15 minutes. If irritation persists, seek medical attention. If skin is sensitive, wear rubber gloves. Do not breathe spray mist. Contains Sodium Hydroxide. CAS #1310-73-2

---

# **NEWBORN BROTHERS CAULK GUN (if needed)**

Rugged, welded steel construction. 3 times the power (10:1 thrust ratio) for easier use. Thumb activated pressure release stops caulking flow instantly. 11 fl. oz, caulking gun with superior thrusting power.

---

## **Stainhandler Econo Pak (20')**

STAINHANDLER ECONO PAK (20') 10 2-FOOT ZINC STRIPS. FREE tube of caulk. One for every econo-pak of Zinc Strips. (20')

[Click to enlarge](#)

Protect the appearance of that new or just cleaned roof with Stainhandler Roof & Deck Cleaner

Minimum order – 20 Feet (Econo Pak)

---

## **Stainhandler Roof and Deck Cleaner**

StainhandlerR Roof & Deck Cleaner is a concentrate designed to clean asphalt shingles and cedar shake roofs, wood decks and fencing quickly and easily. Cleans aprox. 2,000 sq.ft./gal. It does not contain chlorine or bleach. Active ingredient is sodium hydroxide. Easy, quick spray-on and hose off application. Removes dirt, pollen, mildew and algae stains.

Cleans stained cedar shake and asphalt shingle roofs. Cleans pine, cedar, redwood and cypress. StainhandleR Roof & Deck Cleaner makes stained and discolored roofs and decks look like new.

---

## **SUPER SOLV (1gal)**

FOR USE ON: Nylon, acrylic, & wool carpets; Fully cured varnished and oil base paint; rubber; laminated counter tops; metals; glass; brick; wood; concrete; grout; fiberglass; factory baked auto finish except latex. READ ENTIRE LABEL BEFORE USING.

CAUTION: Always test on an inconspicuous area. May damage certain plastics, vinyls, fiberglass & oxidized metal. Eye protection recommended. People with sensitive skin should use solvent resistant gloves.

DIRECTIONS: Pretest: Test on an inconspicuous area. Apply SUPER SOLV to a cloth and rub or blot on material to be removed. Continue application until material dissolves. To prevent smearing, rotate cloth often.

GUM OR GLUE: Pretest. Cut or scrape away excess, apply SUPER SOLV.

FABRIC: Pretest on an inconspicuous area for color fastness.

PAPER LABELS: Pretest. Wet label with SUPER SOLV, wait 1 minute, then remove label.

LATEX PAINTED SURFACES: Pretest. Rub gently to prevent damaging the underlying paint.

HARD SURFACES: Pretest. It may be necessary to use a bristle brush. In such cases, apply SUPER SOLV directly to material to be removed and brush.

CARPETS: Pretest. Apply with cloth. Pouring may damage glue on backing.

DO NOT USE ON PLEXIGLASS, FIBERGLASS, ASTROTURF, URETHANE SURFACES, OR GLAZED TILE.

DANGE: COMBUSTIBLE. Keep away from heat, sparks, flame and static electricity. Do not expose to heat or store at room temperature above 120 F. Use only with adequate ventilation. Vapor is harmful. Eye irritant. Stop use immediately and leave area if strong odor is noticed or if you experience dizziness, headaches, nausea or eye watering. Intentional inhalation can be fatal.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

WARNING: Harmful Or Fatal If Swallowed. Keep out of the reach of children. This product contains Xylene and Methylene Chloride, which are known to the state of California to cause cancer and birth defects or other reproductive harm. Methylene Chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. If used indoors, use only in well-ventilated area. Close container after each use. If swallowed, do not induce vomiting. Call physician immediately. Keep out of reach of children.

---

## **TRUCLEANEX HOUSE WASH (1 GAL)**

IN HAND PUMP SPRAY: Mix 1 part House Wash 3 parts bleach & 16 parts water. A gallon makes 20 gallons. Spray on generous coat. If accumulation is heavy, spray on second coat, wait 10 minutes rinse with hose or pressure wash.

HAND CLEANING – Reduce 8:1 with water. Cleans better, faster, easier, & lasts longer than any other cleaner, and is very economical to use.

TO PRESSURE WASH: Mix 1 part House Wash with 3 parts bleach in a pail. Run through pressure washer at 10:1 ration which will cut House Wash 40:1. Apply a generous coat. Let stand 10 minutes, pressure wash. Cut 40:1 a gallon of House Wash washes 8,800 square feet. Has lowest end use cost of any wash.

TO WASH SURFACES WITHOUT BLEACH – Use 2 parts House Wash, 1 part water and clean as directed above.

NOTE – If the House Wash Concentrate color fades the products ability to perform is not affected. Do not allow to dry on glass, may leave white streaks. White streaks on glass windows are easily removed from the glass with 00 steel wool and water. If bleach is used, protect delicate shrubs and flowers. Test thoroughly before using to be sure surface will not be harmed. Do not get cleaner between thermopane windows.

Contains sodium hydroxide. Avoid contact with eyes. In case of contact flush with water for 15 minutes and get medical attention. Prolonged or repeated contact with skin may cause irritation. Remove contaminated clothing. Wash with soap and water. Get medical attention. Do not breathe sprays mist. Has high pH.

Keep out of reach of children.